

DATE : 404.09.09

NO :

CUST. :

CABLSAZAN YAZD CO.



Specification sheet for cables

Product type	Construction	Standard	Rated voltage	Size
H1Z2Z2-K	Tin-CU/ Cross-Linked LSZH / Cross-Linked LSZH	BS EN 50618 IEC 62930	1500 V DC	1X6
1-No. of cores			1	
2-conductor size (approx.) (mm ²)			6	
3-No. and diameter of wires Tin/CU (N0/mm)			84x0.30	
4-conductor dimension (approx.) (mm)			3.20	
5-Insulation material			Cross-Linked LSZH	
6-Thickness of insulation , nominal (mm)			0.7	
7-Diameter over insulation (approx.) (mm)			4.60	
8-Outer sheath material			Cross-Linked LSZH	
9-Thickness of outer sheath , nominal (mm)			0.8	
10-Diameter of Sheath (approx.) (mm)			6.20	
11-Conductor Dc resistance at 20°C, max (Ω/km)			3.39	
12-Cable color			Red/Black	
13- MARKER: CABLSAZAN YAZD CO . 15613 INSO 131 62930 IEC 131 BSEN 50618 1500 VDC UV-Resistant H1Z2Z2-K 1X4 mm ² Cross-Linked HALOGEN FREE LOW SMOKE MADE IN IRAN 1404 METER				